A1PAMPHLET

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization

International Burcau



(43) International Publication Date 10 February 2005 (10.02.2005)

PCT

(10) International Publication Number WO 2005/013510 A1

(51) International Patent Classification7: H04O 7/20

H04B 7/26,

(21) International Application Number:

PCT/AU2004/000875

(22) International Filing Date:

30 June 2004 (30.06.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 2003904339

4 August 2003 (04.08.2003) ΑU

(71) Applicant (for all designated States except US): BAR-RETT COMMUNICATIONS PTY LTD [AU/AU]; 10 Port Kembla Drive, Bibra Lake, Western Australia 6163 (AU).

(72) Inventor; and


(75) Inventor/Applicant (for US only): BRADSHAW, Phillip [AU/AU]; 10 Port Kembla Drive, Bibra Lake, Western Aus-

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report



nication means. When each receiver means receives a synchronisation signal from the at least one airborne or space-based vehicle each receiver means forwards the synchronisation signal to its respective control means. The respective control means processes the synchronisation signal to determine the operational frequency required by its respective communication means to maintain or establish communication with the other station. The respective control means also operates to control its respective communication means to change to the determined operational frequency.